

## Tripod Turnstile



### Specifications

Model No. JSTZ4802B  
Power supply voltage: AC110V $\pm$ 10% or AC220V $\pm$ 10%, 50Hz/60Hz  
Power: 30W  
Working temperature: -25°C~65°C  
Relative humidity:  $\leq$ 90%, no condensation  
Passing speed: 35 persons/min(normal open)  
30 persons/min(normal close)  
Noise:  $\leq$  65dB  
Application environment: indoor/outdoor  
Protection grade: IP54  
None failure running times:  $\geq$ 3 million times  
Communication distance:  $\leq$ 1200m  
Dimension: 1296mm\*220mm\*980mm  
Maximum channel width: 600mm  
Input interface: DC12V level signal or pulse width $\geq$ 120ms pulse signal,  
driving current  $\geq$ 10mA  
Communication interface: RS485

### Features

- > Slim machine structure, save the installation space.
- > Drawing technology, fine appearance, high class experience.
- > Using special ARM chip and digital orientation technology for more stable control and better arm control accuracy.
- > Three closed circle motor control system and professional digital gear angle detector make the turnstile running smoothly, The lock is sensitive and reliable, arm positioned with high accuracy.
- > Master/slave control system-----good anti-disturb ability, signal transfer is reliable .
- > Multi-control mode for choose, suit different management requirements.
- > Drop arm when power off, lift arm when power on, tele-control arm, drop arm when fire emergency.
- > Alarms when invalid pass.
- > Red and green light display and voice speaker.
- > Counting function: record the passing times and the records can be cleared up from menu
- > Remember the open signal function.
- > Lock the arm when invalid passes.
- > Self-test let solve the problem easy.
- > Reserved standard RS485 communication interface

