KOVIEW KV-B330

- * 2.0 Megapixel
- * Dual bit rate

Overview

Main

* IR Dome Camera



Product introduction

KV-B330 Megapixel HD IR Dome Camera, which adopts digital and progressive scan technology, supports 1920x1080 resolutions without compromising the

image clarity. The image is much clearer than the one of analog camera under the same circumstance. In addition, it is vandal-proof and will automatically

brighten the video image to form a color video under low illumination.

brighten the video image to form a color video under low mullimation.

Dual bit rate: Record in 1920x1080/432×240 locally and CIF remotely

With IR LED

Functions Up and down angle adjustable.

Auto exposure and white balance.

Technique parameters

Image sensor	1/3" CMOS Sensor, 2.0M Pixel
Exposure mode	Automatic exposure and white balance
Lens	2.8, 3.6/4/6/8/12 mm optional
Min. illumination	0.05Lux (color); 0Lux (IR led on)
Focus	Manual
Tilt range	0 to 55°adjustable by manual
Day/Night shift	IR-CUT
Preview resolution	1920x1080
Video compression	MPEG-4/H.264
Video compression bit rate	500Kbps-4Mbps
Video frame rate	50Hz: 25fps(1920x1080/ 432×240)
	60Hz: 30fps(1920x1080/432×240)
Protocol	TCP/UDP/IP/HTTP/FTP/SMTP/DHCP/DNS/ARP/ICMP/POP3/NTP
Communication interface	RJ45,100M Self-adaptive Ethernet Interface
Power input	DC 12V 2A
Back-end equipments	CMS /NVR
Power consumption	Max. 2W
Working temperature	-20~+70°C
Working humidity	10 ~ 85%
Weight	0.42kg
Measurement (WxHxL)	80.0x75.5x145.0mm