



Walk through by Authenticating face with mask and body temperature



Turnstile Type



Wall mounting Type



Ultra User Friendly

- Contactless for ultimate hygiene
- Walk through without stop



High Security

- Video and Photo proof
- Incident Trackable



Robust Performance

- Less than 0.3 second
- Sunlight proof



High Usability

- Pre-enrollment with existing Photo
- Wall mounting or Turnstile installation

VF9000 is a brilliant model of Hanvon visible light face recognition product line. It adopts deep learning algorithm to enable super performance of face recognition which provides fantastic user experience. Equipped with Industrial IPS touch screen and metal casing guarantee high grade of hardware. Diamond and IP65 design allows vast deployment at public areas especially at sports stadium, school, hospital, airport, station, central building.

	VF9000
User Capacity	Standard 10,000 face(1:N) up to 50,000(1:N) optional
Speed	Less than 0.3 second
Accuracy	>99%
Lighting Compatible	0.1Lux~200,000Lux
Working Distance	0.3-3 meter
Record Capacity	80,000
Security Photo	80,000
Authentication	Face , Card+Face, Card/Face, ID+Pin,
Masks Detection	Yes
Temperature Detection	Distance: 30cm~50cm (1ft~1.64ft) Range: 33°C~42°C (91.4°F~107.6°F), Accuracy: ±0.3°C (±32.54°F), indoor without wind
Attendance	Interval, Work Status, Work Code
Operating System	Android 7.1
Processor	Dual Cortex-A72 up to 2.0GHz, Four Cortex-A53 up to 1.5GHz
Screen	8 inch Touch Screen 1280×800
Sensor	2 MP dual lens, white fill light, IR light, and WDR
Storage	2GB Ram, 8GB EMMC Flash
Interface	Wifi, TCP/IP,USB,RS485,RS232,Wiegand Input&Output, Relay, Alarm in&out, Exit Button, Door Sensor
Power	DC12V 2.5A
Working Environment	For terminal: -20°C~70°C(-4°F~158°F), Humidly<95% (non-condensing) Temperature module: 10°C -40°C(50°F~104°F)
Dimension(L*W*H)	180*98*391mm
Weight	6Kg

Hanwang Technology Co., Ltd

Address: Hanvon Tower, ZhongGuanCun, Software Park, Beijing, China, Postcode: 100193

Tel: +86-10-82786682 **Fax:** +86-10-82786862

Email: facego_inquiry@hanwang.com.cn **Http:** //www.hanvon.com

Hanvon®