VidoNet

Color Metal Dome Camera FEATURES

- Flush or Ceiling mount for different environment
- Sony Super HAD CCD
- Provide crisp & ultra sharp colour image
- Compact Design
- Durable metal-type design





SPECIFICATIONS

| Model No. | VTC-605D | VTC-606D |
|----------------------------------|--|------------------------------------|
| Image Device: | 1/3" Sony Super HAD CCD | |
| Total Number of Pixels | 582(H)×512(V) | 752(H)×582(V) |
| Scanning System | 2:1 Interlace 625 lines / 50 fields / 25 frames Horizontal: 15.625 kHz. Vertical: 50 Hz | |
| Synchronization | Internal | |
| Horizontal Resolution | 420 TV lines | 480 TV lines |
| Minimum Illumination | 1 Lux/F1.2 | 1 Lux/F1.2 |
| Signal/Noise Ratio | Better than 46 dB | Better than 50 dB |
| Video Output | 1.0Vp-p 75 ohm | |
| Gamma | r=0.45 | |
| Auto Electronic Shutter | 1/50~1/100,000 S. | |
| Backlight Compensation | Auto | |
| Gian Control | Auto | |
| Lens Type | 2.5mm, 2.9mm, 3.7mm, 6mm | |
| White Balance | Auto | |
| Power Requirement | 12VDC (±10%)160mA | |
| Ambient Operation Temperature | -10°C∼+50°C | |
| Dimension | Wall: Ф87.5 × 84.5 (H) mm | Ceiling: Ф110.6×62.3 (H) mm(Ф75mm) |
| Weight | Approx. 320g | |

^{*}Features and specifications are subject to change without prior notice.

^{*}Fush mount kit included.